

**MDEBond AFT Clear**

November 2023

Description	Clear double sided acrylic foam tape suitable for a wide range of interior and exterior bonding applications and attachments in general industry, printing and signage, DIY, appliances. Suitable for bonding various materials, both LSE (Low Surface Energy) and HSE (High Surface Energy), ABS, PC, PMMA, painted metals, aluminum etc.
Color	Clear
Carrier type	Acrylic foam
Adhesive	Modified Acrylic Adhesive
Total thickness w/o liner	1 mm
Liner	Red film
Color	Translucent
Adhesion to steel (According to PT0002)	>20 N/cm (180° Peel Adhesion: Room temperature, 72hr dwell time Jaw Speed 300mm/min)
Temperature operating range	- 30°C / +110°C
Application instructions	Surfaces must be clean, dry and smooth, free of voids, projections, loose materials, oil, grease, sealers, and all other surface contaminants. More detailed information can be found in the <i>Mounting instruction technical bulletin</i>
Important instructions	The product must be stored in its original packaging in a clean, dry, well ventilated area. Low temperatures at the time of application may increase the possibility of condensation on the surface, which will reduce the final bond strength.

The above given information has been provided by the producer and it should be considered as a guide. Given the variety of factors that can affect the use and performance of the product, user should evaluate to determine its suitability for purpose.